



Screw Type

16~28

36~104

Special standard,

1 BODY

Material : Die cast zinc

Surface treatment : Electro galvanized.

2 LOCKNUT

Material : Steel.

Surface treatment : Electro galvanized.

3 TORQUE SCREW M5(16~54) M6(70~104)

Material : Steel.

Surface treatment : Electro galvanized.

4 GROUNDING SCREW M5-5

Material : Steel.

Surface treatment : Electro galvanized.

5 PACKING

Material : EPT (cap) Black

6 LOCKNUT PACKING

Material : Rekusuran EBA T690 Black

SIZE	16	22	28	36	42	54	70	82	92	104
L	50	54	58	62	66	71	81	89	97	106
l	13.5	14.8	14.8	16.2	17.8	20.0	22.2	25.5	30.0	34.4
D	33	39	46	54	64	79	92	107	123	138
3screw	M5X1	M5X1	M5X1	M5X2	M5X2	M5X2	M6X2	M6X2	M6X2	M6X2
W/g	80	120	150	210	270	460	620	770	1070	1450

Productin OCM

Tehnology control sales JOINT

FILM NAME	F-626-20020511 Auto CAD
DRAWN CHECK APPR ISSUED	NBG-W SET SCREW CONNECTOR joint kogyo T.okano