



SIZE	16S	16	22	28	36	42	54	70	82	92	104
L	84	84	86	96	97	104	120	135	151	158	158
l	19	19	19	24	24	25	26	28	28	30	30
D	34	34	40	49	58	65	80	100	115	130	145
H	32	32	38	46	55	62	76	96	111	126	141
d	12.5	12.5	16.5	21.0	27.0	31.0	39.0	50	58	66	76
W/g	270	270	380	570	800	1100	1900	3200	4900	6000	7400

パッキング φφ (CR)

SIZE	16S	16	22	28	36	42	54	70	82	92	104
A	6-8	11-12	15-16	19-20	24-26	28-30	36-38	46-48	54-56	62-64	72-74
B	5-7	9-11	13-15	17-19	22-24	26-28	34-36	44-46	52-54	60-62	70-72
C	4-5	8-10	12-14	16-18	21-23	25-27	33-35	42-44	50-52	58-60	68-70
D	x	8-9	11-13	15-17	20-22	24-26	32-34	40-42	48-50	56-58	66-68
E	x	x	11-12	14-16	18-20	22-24	30-32	38-40	46-48	54-56	64-66
F	x	x	10-11	13-14	17-18	20-22	28-30	36-38	44-46	52-54	62-64

P-JPX 16S~104 SIZE

使用範囲 (-20℃ to +60℃)

製造 : SFC (GXUZ)

技術指導、管理、販売 JOINT

FILM NAME	C310-20050328 Auto CAD
DRAWN CHECK APPR ISSUED	P-JPX d2G4 joint kogyo T.okano